


Flexible for basic machine duties.



Three-phase AC motor (IE1) for constant and variable movements.

Power range:

0.12 to 45 kW (0.8 to 144 Nm)

Suitable both for mains operation and inverter operation.

Features

- IE1 energy efficient
- Low moments of inertia for high dynamic performance
- Available in the models B3, B5, B14 (4-pole) and as geared motors (2-pole, 4-pole and 6-pole)
- Setting range during inverter operation up to 1:17.4 with constant torque
- Enclosure IP55
- Inverter-compatible windings as standard

IE1 technology – MD AC motors – An overview

Specifications at 50 Hz, 400 V

Size		063	071	080	090	100	112	132	160	180
Rated power	P [kW]	0.12 0.18 0.25	0.25 0.37 0.55	0.55 0.75 1.1	1.1 1.5	2.2 3.0	4.0	5.5 7.5	11 15	18.5 22
Rated current	I [A]	0.49 0.58 0.82	0.75 0.95 1.4	1.4 1.9 2.8	2.8 3.8	5.3 7.2	9.3	11.7 16.5	21 27.8	32.8 38.8
Rated torque	M [Nm]	0.8 1.26 1.74	1.74 2.51 3.74	3.8 5.1 7.5	7.56 10.1	14.6 20.5	26.3	36.2 49.2	71.9 98.1	120 144
Rated speed	n [rpm]	1425 1365 1370	1370 1410 1405	1390 1410 1390	1390 1410	1440 1430	1450	1450 1455	1460 1460	1470 1465

The modular system for your application

Thanks to their flexible modular design, the three-phase AC motors are ideal for use with any application:

- Brake attachments
 - Scalable braking torques
 - Long-life design
 - Various controls
- Feedback systems
 - Resolver
 - Incremental encoder
 - Absolute value encoder
- Self-ventilated or separate blower
- Connection options
 - Plug connectors
 - Terminal box
- Various thermal sensors

Other properties

Degree of protection	EN 60529	IP55
Energy efficiency class	IEC 60034	IE1
Approvals		cURus, GOST-R, CCC and UkrSepro
Temperature class	IEC / EN 60034-1 utilisation	B
	IEC / EN 60034-1 insulation system	F
Climatic conditions	Storage temperature	-30°C to +60°C
	Operating temperature	-20°C to +40°C
Connection	Power connection	Terminal box or plug connectors
	Brake connection	
	Separate fan connection	
	Feedback connection	
Colour		Primed Uncoated Paint in various corrosion-protection designs in accordance with RAL colours